

# CERTIFICATE

This certifies, that the company

**Valland S.p.A.**

**Corso Giacomo Matteotti, 8A**

**23900 Lecco (LC)**

**Italy**

Is authorized to provide the product mentioned below

Description of product: **2-ways bolted side entry trunnion mounted ball valve series A11**

In accordance with: **EN 61508:2010 Parts 1, 2, 4, 5, 6, 7**

Registration No 20 21038 01  
Test Report No PS-25037-24-M-01  
File reference 21038-01



TÜV Nord Italia S.r.l (TÜV NORD Group)  
Via Turati, 70 – 20023 Cerro Maggiore (MI) – Italy

[www.tuev-nord.it](http://www.tuev-nord.it)



Validity  
from 2024-02-16  
until 2027-02-15

Cerro Maggiore, 2024-02-16  
[prodotto@tuev-nord.it](mailto:prodotto@tuev-nord.it)

Type	A
HFT	0
Safety functions	1. Close / Open upon the demand of the actuation system 2. Close upon the demand of the actuation system, with inline tightness when in closed position
Mode of operation	Low Demand Mode

Random failure rates				
Configuration	Safety function	$\lambda_{DU}$ [1/h]	$\lambda_{DD}$ [1/h]	$\lambda_S$ [1/h]
Self-relieving / Double piston effect - No PST	1	4,84E-08	0,00E+00	0,00E+00
Self-relieving / Double piston effect - With PST	1	4,36E-09	4,41E-08	0,00E+00
Self-relieving - No PST	2	5,68E-08	0,00E+00	0,00E+00
Self-relieving - With PST	2	1,27E-08	4,41E-08	0,00E+00
Double piston effect - No PST	2	5,25E-08	0,00E+00	0,00E+00
Double piston effect - With PST	2	8,45E-09	4,41E-08	0,00E+00

Systematic capability	3 (Route 1 <sub>s</sub> applied)			
Architectural constraints	Route 1 <sub>H</sub> :	Applied	Route 2 <sub>H</sub> :	Applied
	The product can be used in: <ul style="list-style-type: none"> <li>single channel configuration:                             <ul style="list-style-type: none"> <li>up to SIL 2 without external diagnostic tests</li> <li>up to SIL 3 considering external diagnostic tests</li> </ul> </li> <li>double channel configuration: up to SIL 3</li> </ul>			
Remarks:	<ul style="list-style-type: none"> <li>Self-relieving configuration: both upstream and downstream seats shall be of self-relieving type (i.e. single barrier in the flow direction)</li> <li>Double piston effect configuration: at least downstream seat shall be of double piston effect type (i.e. double barrier in the flow direction)</li> <li>For further details, including environmental conditions, limitations of use, lifetime, failure rates traceability, mean repair times, common cause factors and systematic capability constraints, make reference to Safety Manual "Safety manual BV"</li> </ul>			

